

# LIBRA HEAD



## The Industry Standard

For more than two decades, the Libra has set the highest industry standard built on a reputation as the most trusted stabilized remote head in the world.


Robust and strong, the Libra is capable of carrying camera packages up to 150 pounds in the most demanding conditions and harsh environments.

Libras are extremely versatile with their mounting capabilities in underslung, overslung, or horizontally mounted matrix mode, and backed with an extensive inventory of custom bracketry constructed to accommodate years of out-of-the-box specialty rigs.

## SPECIFICATIONS


### Dimensions

The minimum width is 21" (53.3 cm) and the minimum depth is 8.5" (21.6 cm). The minimum height is 28" (71 cm) underslung, and 20" (50.8 cm) overslung.




### Weights

The head weighs 56 lbs (25.4 kgs), and the iso-damp weighs 10 lbs (4.5 kgs) for a total weight of 66 lbs (30 kgs). It can carry up to 150 lbs (68 kgs) max camera and accessory payload.



### Ranges

Axis ranges are  $\pm 355^\circ$  pan,  $\pm 360^\circ$  tilt (limited by payload), and  $\pm 40^\circ$  roll. Max pan and tilt speed is  $300^\circ/\text{sec}$ , and max roll speed is  $100^\circ/\text{sec}$ . Operating temperature ranges from  $-22^\circ\text{F}$  ( $-30^\circ\text{C}$ ) to  $113^\circ\text{F}$  ( $+45^\circ\text{C}$ ).



### Accessories

There is a wide variety of optional accessories to help you maximize the use of the Libra, including wireless focus systems, pan bars, wireless boosters, joysticks, handheld simulation units, mini 2-axis conversion kits, and breakaway wheels.

CREATIVITY IN REACH®

[www.procamrentals.com](http://www.procamrentals.com)

(818) 717-0354

[marketing@procamrentals.com](mailto:marketing@procamrentals.com)



# LIBRA HEAD

STABILIZED	<b>Yes</b>
WEIGHT	<b>56 lbs (25.4 kgs)</b>
ISO-DAMP WEIGHT	<b>10 lbs (4.54 kgs)</b>
MAX PAYLOAD	<b>150 lbs (68 kgs)</b>
RANGE	<b>Pan <math>\pm 355^\circ</math>, Tilt <math>\pm 360^\circ</math>, Roll <math>\pm 40^\circ</math></b>
MAX PAN/TILT SPEED	<b>Pan/Tilt 300°/sec, Roll 100°/ sec</b>

UNDERSLUNG MIN HEIGHT	<b>28" (71 cm)</b>
UNDERSLUNG MIN WIDTH	<b>21" (53.3 cm)</b>
UNDERSLUNG MIN DEPTH	<b>8.5" (21.6 cm)</b>
OVERSLUNG MIN HEIGHT	<b>20" (50.8 cm)</b>
OVERSLUNG MIN WIDTH	<b>21" (53.3 cm)</b>
OVERSLUNG MIN DEPTH	<b>8.5" (21.6 cm)</b>

