

LIBRA MINI



Compact Version of the Libra Head

The Libra Mini is smaller and lighter, but comes with the same stabilization technology as the industry standard Libra head.


It can be the perfect option for space-restricted shots inside vehicles, pushing through car and home windows, and/or mounted on weight-restricted rigs.

It is wireless, weather-resistant, and has many of the operational features as the full size version.

SPECIFICATIONS


Dimensions

The minimum width is 11" (27.9 cm) and the minimum depth is 8.9" (22.6 cm). The minimum height is 13" (33 cm) underslung, and 11.5" (29.2 cm) overslung.




Weights

The head weighs 19.5 lbs (8.85 kgs), and the iso-damp weighs 10 lbs (4.5 kgs) for a total weight of 29.5 lbs (13.4 kgs). It can carry up to 25 lbs (11.34 kgs) max payload.



Ranges

Axis ranges are $\pm 355^\circ$ pan, $\pm 360^\circ$ tilt (limited by payload), and $\pm 40^\circ$ roll. Max pan and tilt speeds are 300°/sec, and max roll speed is 100°/sec. Operating temperature ranges from -22°F (-30°C) to 113°F ($+45^\circ\text{C}$).



Accessories

There is a wide variety of optional accessories to help you maximize the use of the Mini, including wireless focus systems, pan bars, wireless boosters, joysticks, handheld simulation units, mini 2-axis conversion kits, and breakaway wheels.

CREATIVITY IN REACH[®]

www.procamrentals.com

(818) 717-0354

marketing@procamrentals.com



LIBRA MINI

STABILIZED	Yes
WEIGHT	19.5 lbs (8.85 kgs)
ISO-DAMP WEIGHT	10 lbs (4.54 kgs)
MAX PAYLOAD	25 lbs (11.34 kgs)
RANGE	Pan $\pm 355^\circ$, Tilt $\pm 360^\circ$, Roll $\pm 40^\circ$
MAX PAN/TILT SPEED	Pan/Tilt 300°/sec, Roll 100°/ sec

UNDERSLUNG MIN HEIGHT	13" (33 cm)
UNDERSLUNG MIN WIDTH	11" (27.9 cm)
UNDERSLUNG MIN DEPTH	8.9" (22.6 cm)
OVERSLUNG MIN HEIGHT	11.5" (29.2 cm)
OVERSLUNG MIN WIDTH	11" (27.9 cm)
OVERSLUNG MIN DEPTH	8.9" (22.6 cm)

