

SCORPIO CLASSIC MINI

Continuous 360° Motion

In 2-axis mode, this remote head weighs 40 pounds, and 55 pounds when a 3rd axis is added. The remote head can be controlled using handwheels, a joystick, or a pan bar.

Repeatable movements, limits, dampening, and speed adjustments for all axes can be independently programmed.

All axis have two internal slip rings that allow them to continuously rotate 360 degrees, as well as transfer all communication, power, video, and auxiliary signals.

SPECIFICATIONS

Dimensions

Without roll cage, the width is 12.6" (31.9 cm) and depth is 7.2" (18.3 cm). With roll cage, the width is 25.1" (63.9 cm) and depth is 25.5" (65 cm). The minimum height is 24.7" (62.8 cm).

Weights




The head weighs 40 lbs (18 kgs) in 2-axis mode, and 77 lbs (35 kgs) in 3-axis mode. It can carry a max payload up to 99 lbs (45 kgs) in 2-axis mode, and 44 lbs (20 kgs) in 3-axis mode.

Ranges

Axis ranges are $\pm 360^\circ$ for both pan and tilt. Max pan, tilt, and roll speed is 144°/sec.

Accessories

It can be operated using handwheels, pan bar, or a joystick. The joystick includes Focus and zoom control directly connected to a servo lens.



CREATIVITY IN REACH®

www.procamrentals.com

(818) 717-0354

marketing@procamrentals.com



SCORPIO CLASSIC MINI



STABILIZED No
WEIGHT 2-Axis: 40 lbs (18 kgs), 3-Axis: 77 lbs (35 kgs)
MAX PAYLOAD 2-Axis: 99 lbs (45 kgs), 3-Axis: 44 lbs (20 kgs)
RANGE Pan $\pm 360^\circ$, Tilt $\pm 360^\circ$
MAX SPEED Pan/Tilt/Roll $144^\circ/\text{sec}$

UNDERSLUNG HEIGHT 24.7" (62.75 cm)
UNDERSLUNG WIDTH 12.56" (31.9 cm)
UNDERSLUNG DEPTH 7.2" (18.3 cm)
UNDERSLUNG CAGE WIDTH 25.1" (63.85 cm)
UNDERSLUNG CAGE DEPTH 25.5" (64.76 cm)

