

TECHNO Z-HEAD

SuperTechnocrane Non-Stabilized Head

The Z-Head is a standard integrated non-stabilized remote head from SuperTechnocrane.

It is fully modular, allowing it to support small compact cameras while being big enough to accommodate some large format cameras.


It can be operated as a 2-axis or 3-axis non-stabilized head using the 3rd axis add-on.

A benefit to the Z-head is the splash-proof enclosure that allows it to be used in even the most demanding conditions.

SPECIFICATIONS


Dimensions

The minimum height is 24" (61 cm), the minimum width is 26" (66 cm), and the minimum depth is 6" (15 cm).




Weights

The head weighs 43 lbs (19.5 kgs), and can carry up to 80 lbs (36.3 kgs) max payload.



Ranges

Axis ranges are $\pm 540^\circ$ pan, $\pm 540^\circ$ tilt (limited by payload), and $\pm 540^\circ$ roll.



Accessories

The Z-Head can be operated using the standard handwheels, pan bars, or a joystick.

CREATIVITY IN REACH®

www.procamrentals.com

(818) 717-0354

marketing@procamrentals.com



TECHNO Z-HEAD

STABILIZED | **No**
WEIGHT | **43 lbs (19.5 kgs)**
MAX PAYLOAD | **80 lbs (36.3 kgs)**

RANGE | **Pan $\pm 540^\circ$, Tilt $\pm 540^\circ$, Roll $\pm 540^\circ$**
POWER | **120 Volts / 20 Amps**

UNDERSLUNG MIN HEIGHT | **24" (61 cm)**
UNDERSLUNG MIN WIDTH | **26" (66 cm)**
UNDERSLUNG MIN DEPTH | **6" (15 cm)**

