

FREEFLY MOVI PRO



Ultra Lightweight and Portable

One of the most advanced ultra-lightweight and portable camera movement systems designed to maximize shooting time in several configurations.


It features high-quality sensors for precise calibration in even the most challenging of shots. Its internal processing and tuning algorithms allow the system to tune the filter and stiffness in ~3 seconds per axis without requiring user input.

Its back screen provides quick access to vital information and the ability to easily tune and adjust parameters without an external device.

SPECIFICATIONS


Dimensions

The minimum width is 13.5" (34.3 cm) and the minimum depth is 13.46" (34.2 cm). The minimum height is 17" (43.2 cm) underslung, and 12" (31 cm) overslung.



Weights

The head weighs only 5.8 lbs (2.65 kgs). It can carry up to 15 lbs (6.8 kgs) max payload.



Ranges

Axis ranges are $\pm 360^\circ$ pan, $+90^\circ$ to -165° tilt, and $\pm 60^\circ$ roll. Max pan and tilt speeds are $360^\circ/\text{sec}$. Max operating speed is 62 mph (100 kph).



Technical

The speed advantages of the Movi Pro system extend to its long-lasting batteries, which can also be quickly hot-swapped to minimize downtime.

CREATIVITY IN REACH®

www.procamrentals.com

(818) 717-0354

marketing@procamrentals.com



FREEFLY MOVI PRO



STABILIZED | **Yes**
WEIGHT | **5.8 lbs (2.65 kgs)**
MAX PAYLOAD | **15 lbs (6.8 kgs)**

RANGE | **Pan $\pm 360^\circ$, Tilt $+90^\circ/-165^\circ$, Roll $\pm 60^\circ$**
MAX SPEED | **Pan/Tilt $360^\circ/\text{sec}$**
MAX OP SPEED | **62 mph (100 kph)**

UNDERSLUNG MIN HEIGHT | **17" (43.2 cm)**
UNDERSLUNG MIN WIDTH | **13.5" (34.3 cm)**
UNDERSLUNG MIN DEPTH | **13.46" (34.2 cm)**

